

Ampatop[®] Seal

Weldable roof membrane



- Weldable with Ampacoll[®] LiquiSeal, solvent THF
- Weldable with hot air
- Material easy to process and lay, pleasant feel
- Can be processed on both sides, no waste
- Monolithic technology

Ampatop[®] Seal 1.5 m

Roll dimensions

Length: 30 m / Width: 1.5 m / Area: 45 m²

Pallet details

22 rolls = 990 m²

Ampatop[®] Seal 2.8 m

Roll dimensions

Length: 20 m / Width: 2.8 m / Area: 56 m²

Pallet details

22 rolls = 1'232 m²

Ampatop[®] Seal Jumbo

Roll dimensions Jumbo 1,5 m

Length: 400 m / Width: 1.5 m / Area: 600 m²

Roll dimensions Jumbo 2,8 m

Length: 400 m / Width: 2.8 m / Area: 1'120 m²



Technical data:


s_D value	0.18 m
Weight	350 g/m ²
Thickness	≥ 1,0 mm
Fire behaviour	E, EN 13 501-1
Tear resistance	
longitudinal	400 N/5 cm
transverse	300 N/5 cm
Tear elongation	
longitudinal	50%
transverse	70%
Resistance to water penetration	W1
Water pressure resistance	> 400 cmWS
Outdoor exposure time	4 months
Minimum roof slope	5°
CE marking	EN 13859-1:2005-05/2010

Application: Weldable roof membrane. Please follow the country-specific norms and ask Ampack about the application.

10

Jahre Garantie
Ans Garantie
Anni Garanzia
Years Warranty

* Security is part of the system at Ampack. We cover the cost of removal and replacement, and consequential damage, as well as the replacement materials.

 **ISO 9001:2008**
Swiss Research



Always use Ampatop® Seal with the right system accessories.

Follow the installation instructions at www.ampatop-seal.biz

1 Ampacoll® LiquiSeal

- Solution welding compound
- Consumption approximately 1 litre per 200 m² of membrane surface
- Can content 1.25 l

2 Ampacoll® LiquiSeal Applicator

- Bottle and brush for easy application of Ampacoll® LiquiSeal on Ampatop® Seal
- Volume: 500 ml
- Includes brush

3 Ampacoll® TubeSeal

- Prefabricated sleeves for quick ceiling of standard pipe entries
- Diameter: 80 – 120 mm
- Weldable
- Maximum roof slope: 25°

4 Ampacoll® ND.Band

7 Ampacoll® ND Duo

- Nail seals
- ND Duo prescribed for use, if:
 - Roof slope <25° and/or
 - Altitude >800 m

5 Ampacoll® DoubleSeal

- Double-sided adhesive acrylic tape
- Moisture resistant
- Ideal for sheet metal and other flat surfaces

6 Ampacoll® XT 60 mm

- Moisture-resistant acrylic adhesive tape
- For fastening Ampatop® Seal at pipe entries in conjunction with Ampacoll® TubeSeal sealing tape